

## **MATERIAL SAFETY DATA SHEET**

### **(AUSPLY) PLYWOOD / OVERLAID FORMWORK PLYWOOD**

#### **WOOD VENEER PRODUCT**

**IMPORTANT NOTICE:** This Material Safety Data Sheet (MSDS) is written by Ausply in accordance with Worksafe Australia Guidelines. As such, the information contained herein must not be altered, deleted or added to. Ausply will issue a new MSDS when there is a change in product specifications and/or Worksafe Australia guidelines/regulations. Ausply will not accept responsibility for any changes made to its MSDS in content by any other person.

#### **IDENTIFICATION:**

**Product Name:** Ausply Structural Plywood - AS/NZS2269;  
Overlaid Formwork Plywood AS6669

**UN Number:** None allocated

**Registered Trade Name:** None allocated

**Dangerous Goods Class:** None allocated

**Hazchem Code:** None allocated

**Poisons Schedule:** None allocated

**Use:** Residential, commercial, industrial and marine construction, furniture and fitments and/or general purpose building material.

#### **PHYSICAL DESCRIPTION/PROPERTIES**

##### **Appearance:**

The products are manufactured as pressed boards ranging in standard thickness from 4mm to 50mm. They are made from wood veneers of a range of species which are bonded together with resin.

**Odour:**

No distinctive odour. Newly manufactured plywood and freshly machined surfaces tend to have the odour of the wood species from which the plywood is manufactured.

<b>Boiling Point</b>	Not applicable
<b>Vapour Pressure</b>	Not applicable
<b>Vapour Density</b>	Not applicable
<b>Melting Point</b>	Not applicable
<b>Solubility in Water</b>	Highly insoluble
<b>Flashpoint</b>	Not applicable
<b>Specific Gravity</b>	0.50-1.00
<b>Flammability in air</b>	Fine airborne dust, generated when the product is machined, can ignite spontaneously
<b>Auto Ignition Temperature</b>	>220°C

**Ingredients:**

<b>Substance/Chemical Entity</b>	<b>CAS No.</b>	<b>Properties by weight</b>
Wood veneer	None	>92%
Phenol formaldehyde resin or	40798-65-0	<8%
Melamine urea formaldehyde resin, or	25036-13-9	<8%
Urea formaldehyde resin	9011-05-6	<8%

**NOTE:**

The above ingredients are bonded together under heat and pressure. The process cures the resin. However, small amounts of formaldehyde may be released from the finished product. In newly manufactured plywood, which is the worst case scenario, formaldehyde emission has been measured in the range 0.03-0.05ppm using the large scale chamber test material.

## **HEALTH HAZARD INFORMATION**

### **Health Effects**

**This product, in its natural form, is not classified as hazardous according to criteria of Worksafe Australia.**

In well ventilated storage areas and work places utilising these products the concentration of formaldehyde in the air will not exceed the World Health Organisation standard of 0.1ppm for the general environment and it will be well below the Worksafe Australia occupational Exposure Standard of 1.0ppm on a time weighted average (twa).

Sealing plywood with paint, varnish or other surface finishes further reduces any emissions.

The known health effects of the constituents of the boards are as follows:

#### **Cured resin:**

The cured resin is inert and not likely to contribute to health effects.

#### **Formaldehyde:**

Formaldehyde gas is irritating to the nose and throat, eyes and skin. It is recommended that storage areas be well ventilated to avoid any irritating effects of a build-up of formaldehyde.

Worksafe Australia has classified formaldehyde as a Category 3 carcinogen - possibly carcinogenic to humans - on the basis of evidence that inhalation of gas caused nasal cancer in experiments with rats. In the experiments, groups of rats were exposed to formaldehyde for six hours a day, five days a week for up to two years at concentrations of 0, 2.0, 5.6 and 14.3ppm. Fifty percent of those exposed at 14.3ppm, one percent exposed to 5.6ppm, but none exposed to 2.0 or 0ppm developed nasal cancers.

There have been more than thirty epidemiological studies involving over 150,000 people occupationally exposed to formaldehyde. These, and studies of behaviour to toxicity, indicate that exposure to formaldehyde below the Worksafe Australia occupational Exposure Standard of 1ppm TWA (time weighted average) will not result in an increased risk of cavity cancers in humans.

As plywood products have emission levels of 0.03 to 0.05 ppm well below the WHO recommended level of 0.1 ppm, under reasonably foreseeable circumstances it is unlikely that the presence of traces of formaldehyde in the product poses a health risk.

#### **Wood Dust:**

When the boards are machined (sawn, sanded, drilled, routed, planed, etc.) wood dust is produced. Wood dust and splinters may cause irritation of the nose and throat, eyes and skin. Some woods may also be sensitizers, and some people may develop allergic dermatitis or asthma. Inhalation of wood dust, both hardwood and softwood, may increase the risk of nasal and Para nasal sinus cancers.

**Exposures to the wood dust produced from machining the boards may result in the following: health effects**

**Acute:**

**Swallowed:** Unlikely to occur, but swallowing the wood dust may result in abdominal discomfort.

**Eye:** The wood dust may be irritating to the eyes causing discomfort and redness.

**Skin:** The wood dust may irritate the skin, resulting in itching and occasionally a red rash. Allergic contact dermatitis may occur.

**Inhaled:** The wood dust may irritate the throat and lungs especially in people with upper respiratory tract or chest complaints. Asthma may occur.

**Chronic:**

Repeated exposures over many years to uncontrolled wood dust from these boards may increase the risk of allergies, dermatitis, asthma or chronic nose or throat irritation in some people. The risk of nasal or Para nasal sinus cancers may also be increased. If the work practices noted in this MSDS are followed, no chronic health effects are anticipated.

**First Aid:**

**Swallowed:** Drink a glass of water.

**Eye:** Flush with flowing water for at least 15 minutes, and if symptoms persist seek immediate medical attention.

**Skin:** Wash with mild soap and running water.

**Inhaled:** Leave the dusty area.

**Advice to Doctor:** Treat symptomatically.

**PRECAUTIONS FOR USE**

**Exposure Standards:**

The Worksafe Australia Exposure Standards for softwood (e.g. pine) dust, published in October 1991, are:

5 mg/m<sup>3</sup> time-weighted average (TWA)  
10mg/m<sup>3</sup> short term exposure limit (STEL)

and hardwood are

1 mg/m<sup>3</sup> time weighted average (TWA)  
2 mg/m<sup>3</sup> short term exposure limit (STEL)

Wood dust is also listed as a sensitizer and the Exposure Standard is under review. In the interests of maintaining a safe working environment, it is recommended that workplace exposures to wood dust should not exceed 1.0 mg/m<sup>3</sup> TWA.

### **Engineering Controls:**

All work with these boards should be carried out in such a way as to minimise the generation of wood dust.

Under factory conditions, machining should be done with equipment fitted with exhaust devices capable of removing wood dust at the source. Hand power tools should be fitted with dust bags.

Work areas should be well ventilated. They should be cleaned at least daily, and wood dust should be removed by vacuum cleaning or by the wet sweeping method.

### **Skin Protection:**

Wear loose, comfortable clothing. Long-sleeved shirts, trousers and comfortable work gloves (AS2161) should be worn if skin irritation occurs.

After handling boards, wash with mild soap and water. Do not scratch or rub the skin if it becomes irritated.

Wash work clothes regularly and if possible separate from other clothes.

### **Respiratory Protection:**

If wood dust exposures are not controlled when machining (sawing, routing, planing, drilling, sanding, etc.) a class P1 or P2 replaceable filter or disposable face piece respirator should be worn. Respirators should comply with AS/NZS1716, and be selected, used and maintained in accordance with AS/NZS1715.

### **Eye Protection:**

Safety glasses or non-fogging goggles (AS/NZS1337) should be worn when machining.

### **Flammability:**

These boards are flammable but difficult to ignite.

Avoid a build-up of wood dust and keep all storage and work areas well ventilated.

Avoid sources of radiant heat and flame, and avoid sparks and sources of ignition in all electrical equipment, including dust extraction equipment.

People must not smoke in storage or work areas.

## **SAFE HANDLING INFORMATION**

### **Storage and Transport:**

The boards should be stored in well ventilated areas away from source of heat, flames or sparks.

No special transport requirements are considered necessary.

### **Spills and Disposals:**

Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites, or burnt in an approved furnace or incinerator, in accordance with disposal authority guidelines.

Wood dust should be cleaned up by vacuuming or wet sweeping.

### **Fire/Explosion Hazard:**

Early fire hazard properties as determined in accordance with AS1530 Part 3.

<b>Ignitability Index</b>	14
<b>Spread of Flame Index</b>	8
<b>Heat Evolved Index</b>	8-10
<b>Smoke Developed Index</b>	2-3

Burning or smoldering boards or wood dust can generate carbon dioxide and other pyrolysis products typical of burning organic material. Dry wood dust in high concentrations can be explosive. Use water or dry chemical powder fire extinguishers:

**Contact Point:****NAME:** Mr. Craig Jones**TITLE:** Sales Manager**COMPANY:** Ausply Pty Ltd**ADDRESS:** 128 Elizabeth Avenue, FOREST HILL 2651**PHONE NUMBER:** (02) 6922 7274**FAX NUMBER:** (02) 6922 7284

"Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information".

## **WOOD DUST - PLYWOOD PRODUCTS**

### **(1) PRODUCT WARNING LABEL**

The following warning label is to be legibly affixed at least once to each plywood panel.

#### **WARNING:**

**AVOID BREATHING WOOD DUST : AVOID CONTACT WITH THE EYES**

### **(2) PACK WARNING LABEL**

#### **WARNING**

Wood dust produced by machining or sanding wood products including plywood, may cause irritation to the eyes, nose and throat. It may also cause sensitization, e.g. dermatitis and asthma. Repeated and prolonged exposure to wood dust may cause nasal cancer.

**AVOID BREATHING WOOD DUST : AVOID CONTACT WITH EYES**

Work in a clean, well ventilated area with machines that are equipped with efficient dust extraction systems or, if these are not available wear an Australian/New Zealand Standards approved dust mask and eye protection.

Respirators/dust masks should comply with AS/NZS1716 and be selected and maintained in accordance with AS/NZS1715. Safety glasses or non-fogging goggles to AS/NZS1337 should be worn when machining these products.