

Section 1 - Identification of The Material and Supplier

Acrylic Technologies Australia Pty Ltd
Unit 4, 128 Station Road
Seven Hills NSW 2147 AUSTRALIA

Phone: 02 9674 3005
Fax: 02 9674 8005

Chemical nature: Adhesive
Trade Name: ACRIFIX 190
Product Use: Adhesive for plastics
Creation Date: August, 2017
This version issued: June, 2018 and is valid for 5 years from this date.
Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. F, Flammable. Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S6

ADG Classification: Class 3: Flammable liquids.

UN Number: 1133, ADHESIVES containing flammable liquid



GHS Signal word: DANGER

Flammable liquids Category 2
Skin Irritation Category 2
Skin Sensitisation Category 1
Eye irritation Category 2B
Specific Target Organ Toxicity - Single Exposure Category 3

HAZARD STATEMENT:

H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H320: Causes eye irritation.
H335: May cause respiratory irritation.

PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical ventilating, lighting and other equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing fumes, mists, vapours or spray.
P262: Do not get in eyes, on skin, or on clothing.
P264: Wash contacted areas thoroughly after handling.
P271: Use only outdoors or in a well ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P363: Wash contaminated clothing before reuse.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P333+P313: If skin irritation or rash occurs: Get medical advice.
P381: Eliminate all ignition sources if safe to do so.

SAFETY DATA SHEET

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

STORAGE

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Slightly violet viscous liquid

Odour: Ester-like odour

Major Health Hazards: irritating to respiratory system and skin, possible skin sensitiser.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Methyl methacrylate	80-62-6	>60	208	416
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses. Avoid the use of water fog.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 10°C, Abel-Pensky CC

SAFETY DATA SHEET

Upper Flammability Limit: 12.5%
Lower Flammability Limit: 2.1%
Autoignition temperature: 430°C
Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include butyl rubber, neoprene. Eye/face protective equipment should comprise, as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Methyl methacrylate	208	416

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: butyl rubber, neoprene.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

SAFETY DATA SHEET

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Slightly violet viscous liquid
Odour:	Ester-like odour
Boiling Point:	Boils at about 100°C at 100kPa.
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No data.
Vapour Pressure:	Approx 4 kPa at 20°C
Vapour Density:	Heavier than air
Specific Gravity:	Approx 1.02 at 20°C
Water Solubility:	Approx 16 g/L at 20°C
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	430°C

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Methyl Methacrylate is classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Methyl Methacrylate	Conc>=20%: Xi; R37/38; R43
	<ul style="list-style-type: none">• Flammable liquid – category 2• Specific target organ toxicity (single exposure) – category 3• Skin irritation – category 2• Skin sensitisation – category 1

Potential Health Effects

Persons sensitised to methyl methacrylate should avoid contact with this product.

Inhalation:

Short Term Exposure: This product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased if treatment is prompt.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

SAFETY DATA SHEET

Eye Contact:

Short Term Exposure: This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is not harmful. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Methyl Methacrylate is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1133, ADHESIVES containing flammable liquid

Hazchem Code: •3YE

Special Provisions: None allocated

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packing Group: II

Packing Instruction: P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredient: Methyl methacrylate, is mentioned in the SUSMP.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer

SAFETY DATA SHEET

NOS Not otherwise specified
NTP National Toxicology Program (USA)
SUSMP Standard for the Uniform Scheduling of Medicines & Poisons
UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, June, 2018.

<http://www.kilford.com.au/> Phone (02)8321 8866

SAFETY DATA SHEET