

# **Material Safety Data Sheet**

Trinseo Australia Pty. Ltd.

Product Name: STYRON\* 470 Natural Polystyrene Issue Date: 20.10.2014
Print Date: 15 Apr 2016

Trinseo Australia Pty. Ltd. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Product and Company Identification

#### **Product Name**

STYRON\* 470 Natural Polystyrene

#### Identified uses

A polystyrene plastic - For industrial conversion as a raw material for manufacture of articles or goods.

#### **COMPANY IDENTIFICATION**

Trinseo Australia Pty. Ltd. ABN 54141196330 541-583 Kororoit Creek Road Altona, VI 3018 Australia

Customer Information Number: +603 7965 53 19

SDSQuestion@trinseo.com

#### **EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 1800-033-882 **Local Emergency Contact:** 1800 033 882

For advice, contact a doctor (at once) or the Australian Poisons Information Centre: 131 126

## 2. Hazards Identification

HAZARDOUS SUBSTANCES CLASSIFICATION: Not classified as hazardous to health according to the criteria of the National Occupational Health and Safety Commission, Australia

# 3. Composition Information

Component	Amount	Classification:	CAS#	EC#
White mineral oil (petroleum)	<= 5.0 %	Not classified.	8042-47-5	232-455-8
Styrene, 1,3-butadiene copolymer	>= 95.0 %	Not classified.	9003-55-8	Polymer

®(TM)\*Trademark

## 4. First Aid Procedures

## **Description of first aid measures**

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Skin Contact:** Wash skin with plenty of water. Seek first aid or medical attention as needed. If molten material comes in contact with the skin, do not apply ice but cool under ice water or running stream of water. DO NOT attempt to remove the material from skin. Removal could result in severe tissue damage. Seek medical attention immediately. Suitable emergency safety shower facility should be immediately available.

**Eye Contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.

## Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### Indication of immediate medical attention and special treatment needed

If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire Fighting Measures

### Suitable extinguishing media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

### Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon dioxide. Carbon monoxide.

**Unusual Fire and Explosion Hazards:** Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is produced when product burns.

### Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

See Section 9 for related Physical Properties

## 6. Accidental Release Measures

**Personal precautions, protective equipment and emergency procedures:** Spilled material may cause a slipping hazard. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Sweep up. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

## 7. Handling and Storage

### Handling

General Handling: No smoking, open flames or sources of ignition in handling and storage area. Good housekeeping and controlling of dusts are necessary for safe handling of product. Avoid breathing process fumes. Use with adequate ventilation. When appropriate, unique handling information for containers can be found on the product label. Workers should be protected from the possibility of contact with molten resin. Do not get molten material in eyes, on skin or clothing. Keep away from heat, sparks and flame. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, electrically bond and ground equipment and do not permit dust to accumulate. Dust can be ignited by static discharge. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

#### Storage

Store in a dry place. Store in accordance with good manufacturing practices.

## 8. Exposure Controls / Personal Protection

### **Exposure Limits**

Although some of the additives used in this product may have exposure guidelines, these additives are encapsulated in the product and no exposure would be expected under normal handling conditions.

#### **Personal Protection**

**Eye/Face Protection:** Use safety glasses (with side shields). If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

**Skin Protection:** No precautions other than clean body-covering clothing should be needed. **Hand protection:** Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task. Use gloves with insulation for thermal protection, when needed.

**Respiratory Protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. Use an approved air-purifying respirator when vapors are generated at increased temperatures or when dust

**Product Name:** STYRON\* 470 Natural Polystyrene

or mist is present. The following should be effective types of air-purifying respirators: When dust/mist are present use a/an Particulate filter. When combinations of vapors, acids, or dusts/mists are present use a/an Organic vapor cartridge with a particulate pre-filter.

**Issue Date: 20.10.2014** 

**Ingestion:** Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

### **Engineering Controls**

**Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

#### Other Information

Selection and use of personal protective equipment should be in accordance with the recommendations in one or more of the relevant Australian/New Zealand Standards, including:

AS/NZS 1336: Recommended practices for eye protection in the industrial environment.

AS/NZS 1337: Eye protectors for industrial applications.

AS/NZS 1715: Selection, use and maintenance of respiratory protective devices.

AS/NZS 2161: Occupational protective gloves. AS/NZS 2210: Occupational protective footwear.

AS 2919: Industrial clothing.

## 9. Physical and Chemical Properties

**Appearance** 

Physical State Pellets or Granules

ColorNaturalOdorOdorless

Odor Threshold No test data available

**pH** Not applicable

Melting Point No test data available

Freezing Point Not applicable
Boiling Point (760 mmHg) Not applicable.
Flash Point - Closed Cup Not applicable

**Evaporation Rate (Butyl** No test data available

Acetate = 1)

Flammability (solid, gas) No

Flammable Limits In Air Lower: Not applicable

**Upper**: Not applicable

Vapor PressureNot applicableVapor Density (air = 1)Not applicableSpecific Gravity (H2O = 1)1.04 - 1.06 Literature

Solubility in water (by Negligible

weight)

**Partition coefficient, n-**No data available for this product.

octanol/water (log Pow)

Autoignition TemperatureNo test data availableDecompositionNo test data available

**Temperature** 

Kinematic Viscosity
Explosive properties
Oxidizing properties
Molecular Weight
No test data available
No test data available
No test data available
No test data available

# 10. Stability and Reactivity

### Reactivity

No dangerous reaction known under conditions of normal use.

### **Chemical stability**

Stable under recommended storage conditions. See Storage, Section 7.

## Possibility of hazardous reactions

Polymerization will not occur.

**Conditions to Avoid:** Avoid temperatures above 300 °C. Exposure to elevated temperatures can cause product to decompose.

Incompatible Materials: None known.

## **Hazardous decomposition products**

Decomposition products depend upon temperature, air supply and the presence of other materials. Processing may release fumes and other decomposition products. At temperatures exceeding melt temperatures, polymer fragments can be released. Fumes can be irritating. Decomposition products can include and are not limited to: Combustible gases.

## 11. Toxicological Information

#### **Acute Toxicity**

## Ingestion

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking if swallowed.

Single dose oral LD50 has not been determined.

Typical for this family of materials. Estimated. LD50, rat > 5,000 mg/kg

### **Aspiration hazard**

Based on physical properties, not likely to be an aspiration hazard.

### **Dermal**

No adverse effects anticipated by skin absorption.

The dermal LD50 has not been determined.

Typical for this family of materials. Estimated. LD50, rabbit > 2,000 mg/kg

## Inhalation

No adverse effects are anticipated from single exposure to dust. Vapors released during thermal processing may cause respiratory irritation.

The LC50 has not been determined. .

#### Eye damage/eye irritation

Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

#### Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin. Mechanical injury only. Under normal processing conditions, material is heated to elevated temperatures; contact with the material may cause thermal burns.

## Sensitization

#### Skin

No relevant data found.

### Respiratory

No relevant data found.

## **Repeated Dose Toxicity**

Additives are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

### **Chronic Toxicity and Carcinogenicity**

No relevant data found.

## **Developmental Toxicity**

No relevant data found.

Product Name: STYRON\* 470 Natural Polystyrene

Reproductive Toxicity
No relevant data found.
Genetic Toxicology
No relevant data found.

## 12. Ecological Information

## **Toxicity**

Not expected to be acutely toxic, but material in pellet or bead form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

## **Persistence and Degradability**

This water-insoluble polymeric solid is expected to be inert in the environment. Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

### **Bioaccumulative potential**

**Bioaccumulation:** No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

### Mobility in soil

**Mobility in soil:** In the terrestrial environment, material is expected to remain in the soil., In the aquatic environment, material will sink and remain in the sediment.

## 13. Disposal Considerations

For uncontaminated material the disposal options include mechanical and chemical recycling or energy recovery. In some countries landfill is also allowed. For contaminated material the options remain the same, although additional evaluation is required. For all countries the disposal methods must be in compliance with national and provincial laws and any municipal or local by-laws. All disposal methods must be in compliance with the EU framework Directives 2008/98/EC and their subsequent adaptations, as implemented in National Laws and Regulations, as well as EU Directives dealing with priority waste streams. Transboundary shipment of wastes must be in compliance with Regulation (EC) No 1013/2006 and subsequent modifications. For non-EU countries, transboundary shipments of wastes must be in compliance with the Basel Convention, as implemented nationally. As a service to our customers, we can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Please contact our Customer Information Group (telephone number in Section 1 of this document) for further details.

# 14. Transport Information

**ADG Non-Bulk** 

**NOT REGULATED** 

ADG Bulk

**NOT REGULATED** 

**IMDG** 

**NOT REGULATED** 

**Issue Date: 20.10.2014** 

#### ICAO/IATA

**NOT REGULATED** 

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

## 15. Regulatory Information

## Australia. Industrial Chemical (Notification and Assessment) Act

The principal components and additives of this product are included in the Australian Inventory of Chemical Substances (AICS) or comply with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989.

### **Classification and User Label Information**

No regulatory requirements known.

## 16. Other Information

#### **Product Literature**

Additional information on this product may be obtained by calling your sales or customer service contact.

#### Revision

Identification Number: 79723 / 4801 / Issue Date 20.10.2014 / Version: 7.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

## Legend

N/A	Not available	
W/W	Weight/Weight	
OEL	Occupational Exposure Limit	
STEL	Short Term Exposure Limit	
TWA	Time Weighted Average	
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.	
DOW IHG	Dow Industrial Hygiene Guideline	
WEEL	Workplace Environmental Exposure Level	
HAZ_DES	Hazard Designation	

Trinseo Australia Pty. Ltd. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have